

**Benefits**

- Ultimate in carbon cartridges
- No carbon fines and superior contaminant capacity.
- Flow rates up to 40 litres per minute.
- Available in 0.5, 1, 2, 5, 10 microns.
- 3 length options – 5, 10, 20 inch.
- 2 diameter options – Standard, Maxi Plus.
- Temperature up to 85°C.

The superior range of Puretec CB Series carbon cartridges are an example of the leading edge technology available through Puretec. CB cartridges are constructed from bonded activated carbon, offering superior treatment of water with no release of carbon fines. The cartridges are highly effective in reducing, taste, odour, chlorine, and sediment. Cyst, lead, heavy metal, high turbidity and sulphur removal models are also available. The ultimate for beautiful drinking water.

Code	Size inches	Micron rating	Diameter	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
CB955	5"	0.5	standard	cyst reduction		8	12	56.71
CB9451-HT	10"	0.45	standard	special size, cyst reduction , 1/4" thread connection		13	12	109.97
CB019	9"	1	standard	cyst reduction		15	12	78.24
CB951	10"	0.5	standard	cyst reduction	POPULAR	15	12	67.17
CB951-H	10"	0.5	standard	cyst heavy metal removal		15	12	75.91
CB011	10"	1	standard	cyst reduction		15	12	60.21
CB051	10"	5	standard		POPULAR	16	12	41.31
CB051-SL	10"	5	standard	slimline diameter		16	12	63.59
CB101	10"	10	standard			18	12	38.14
CB952	20"	0.5	standard	cyst reduction		28	6	92.15
CB052	20"	5	standard			30	6	76.29
CB102	20"	10	standard			32	6	76.29
CB95MP1	10"	0.5	maxi plus	cyst reduction		20	4	143.65
CB05MP1	10"	5	maxi plus			21	4	115.35
CB10MP1	10"	10	maxi plus			23	4	83.88
CB05MP2	20"	5	standard			41	4	237.31
CB95MP2	20"	0.5	maxi plus	cyst reduction		40	4	287.30
CB10MP2	20"	10	maxi plus			42	4	219.63

**Benefits**

- Low pressure, low pressure drop and high flow capabilities i.e. rainwater by gravity feed.
- Suitable for mains and pump pressure.
- Flow rates up to 110 litres per minute.
- 2 length options – 10, 20 inch.
- 2 Diameter options – Standard, Maxi Plus.
- Resistant to bacterial attack.
- Temperature up to 66°C.

The Puretec DP Series Dual-Purpose Long-Life cartridges using special RBC material, features the advantage of being suitable for non-chlorinated and chlorinated water. The RBC media has special porosity and surface area filtration characteristics that in effect means flow and pressure restrictions are minimised. The DP's are ideal for rainwater tanks, bores, whole house, polishing filters on reverse osmosis machines, drinking water and many other applications where sediment down to 10 microns, rust, taste, odour, and slight colour removal is required.

Code	Size inches	Micron rating	Diameter	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
DP101	10"	10	standard		POPULAR	25	24	31.78
DP102	20"	10	standard			50	12	52.23
DP10MP1	10"	10	maxi plus		POPULAR	60	8	79.01
DP10MP2	20"	10	maxi plus			110	6	130.93