

**Benefits**

- 3 times longer life than comparable cartridges.
- Graded depth filtration.
- Protects appliances and health with sediment free water.
- Flows up to 180 litres per minute.
- Available in 1, 5, 10, 20, 50, 75 microns.
- 5 length options – 5, 10, 20, 30 , 40 inch.
- 2 diameter options – Standard, Maxi Plus.
- Temperature rating up to 64°C.

The economical Puretec PX Series cartridges are constructed from virgin polypropylene which is spun and melted simultaneously. This innovative technique means there is no centre core to restrict filter performance. Precise depth filtration is achieved through graded density construction. The PX Series are compatible with most liquids and are highly effective for sediment, rust, sand, silt, algae removal. PX cartridges have no chemical residues. Extra high performance and absolute rated cartridges available.

Code	Size inches	Micron rating	Diameter	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl. GST
PX055	5"	5	standard			14	20	7.99
PX019	9"	1	standard			26	40	18.91
PX059	9"	5	standard			27	40	18.91
PX011	10"	1	standard			27	40	10.86
PX051	10"	5	standard			28	40	10.86
PX101	10"	10	standard			32	40	10.86
PX201	10"	20	standard			34	40	10.86
PX501	10"	50	standard			38	40	10.86
PX751	10"	75	standard			40	40	10.86
PX011-2	10"	1	standard	twinpack		27	20	21.73
PX051-2	10"	5	standard	twinpack	POPULAR	28	20	21.73
PX101-2	10"	10	standard	twinpack		32	20	21.73
PX201-2	10"	20	standard	twinpack	POPULAR	34	20	21.73
PX501-2	10"	50	standard	twinpack	POPULAR	38	20	21.73
PX011-A	10"	1	standard	absolute rating, cyst reduction		25	12	74.66
PX011-H	10"	1	standard	high performance		29	40	17.42
PX051-H	10"	5	standard	high performance		30	40	16.55
PX101-H	10"	10	standard	high performance		33	40	16.55
PX201-H	10"	20	standard	high performance		34	40	16.55
PX501-H	10"	50	standard	high performance		39	40	16.55
PX751-H	10"	75	standard	high performance		41	40	16.55
PX012	20"	1	standard			54	20	23.03
PX052	20"	5	standard			56	20	21.71
PX102	20"	10	standard			64	20	21.71
PX202	20"	20	standard			67	20	21.71
PX502	20"	50	standard			72	20	21.71
PX752	20"	75	standard			76	20	21.71
PX012-A	20"	1	standard	absolute rating, cyst reduction		50	12	149.32
PX012-H	20"	1	standard	high performance		58	20	34.85
PX052-H	20"	5	standard	high performance		60	20	33.09
PX102-H	20"	10	standard	high performance		66	20	33.09
PX202-H	20"	20	standard	high performance		68	20	33.09
PX502-H	20"	50	standard	high performance		78	20	33.09
PX752-H	20"	75	standard	high performance		82	20	33.09
PX01MP1	10"	1	maxi plus			75	10	67.42
PX05MP1	10"	5	maxi plus			76	10	58.76
PX20MP1	10"	20	maxi plus			84	10	58.76
PX50MP1	10"	50	maxi plus			90	10	58.76
PX75MP1	10"	75	maxi plus			94	10	68.59
PX01MP2	20"	1	maxi plus			152	10	134.84
PX05MP2	20"	5	maxi plus			156	10	99.28
PX20MP2	20"	20	maxi plus			164	10	99.28
PX50MP2	20"	50	maxi plus			180	10	99.28
PX75MP2	20"	75	maxi plus			188	10	137.17

Sediment Filter Cartridges

PX SERIES

POLYSPUN SEDIMENT CARTRIDGES / GRADED DEPTH



Code	Size inches	Micron rating	Diameter	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
PX 013-IN	30"	1	standard	Industrial, label		81	20	32.59
PX 053-IN	30"	5	standard	Industrial, label		84	20	32.59
PX 103-IN	30"	10	standard	Industrial, label		96	20	32.59
PX 203-IN	30"	20	standard	Industrial, label		102	20	32.59
PX 503-IN	30"	50	standard	Industrial, label		114	20	32.59
PX 753-IN	30"	75	standard	Industrial, label		120	20	32.59
PX 014-IN	40"	1	standard	Industrial, label		108	20	43.45
PX 054-IN	40"	5	standard	Industrial, label		112	20	43.45
PX 104-IN	40"	10	standard	Industrial, label		128	20	43.45
PX 204-IN	40"	20	standard	Industrial, label		136	20	43.45
PX 504-IN	40"	50	standard	Industrial, label		152	20	43.45
PX 754-IN	40"	75	standard	Industrial, label		160	20	43.45
PX 013-H-IN	30"	1	standard	High performance		81	20	49.66
PX 053-H-IN	30"	5	standard	High performance		84	20	49.66
PX 103-H-IN	30"	10	standard	High performance		93	20	49.66
PX 203-H-IN	30"	20	standard	High performance		96	20	49.66
PX 503-H-IN	30"	50	standard	High performance		111	20	49.66
PX 014-H-IN	40"	1	standard	High performance		108	20	66.21
PX 054-H-IN	40"	5	standard	High performance		112	20	66.21
PX 104-H-IN	40"	10	standard	High performance		124	20	66.21
PX 204-H-IN	40"	20	standard	High performance		128	20	66.21
PX 504-H-IN	40"	50	standard	High performance		148	20	66.21

Sediment Filter Cartridges

RB SERIES

RESIN BONDED SEDIMENT CARTRIDGES



**Benefits**

- Graded density resin bonded technology for longer life.
- Mellamine and Phenolic based cartridges for excellent chemical resistance.
- Available in 5, 10, 25, 50, 125 micron.
- 2 length options – 10, 20 inch.
- Flow rates up to 30 litres per minute.
- Temperatures up to 120°C.

Puretec RB Series cartridges are produced from fibres intrinsically bonded together to create a solid, durable and porous structure. The mellamine (white) models are suitable for drinking water, beverages, cosmetics, liquids and chemicals, while the phenolic (brown) models are designed for chemicals including photographic solutions, chemical spraying, nozzle protection, paints and ink.

Code	Size inches	Micron rating	Diameter	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
RB051	10"	5	standard			31	24	18.47
RB251	10"	25	standard			39	24	18.47
RB501	10"	50	standard			42	24	18.47
RB051-2	10"	5	standard	twinpack	<b>POPULAR</b>	31	12	34.18
RB251-2	10"	25	standard	twinpack	<b>POPULAR</b>	39	12	34.18
RB501-2	10"	50	standard	twinpack		42	12	34.18
RB051-P	10"	5	standard	phenolic based		31	24	28.70
RB101-P	10"	10	standard	phenolic based		34	24	28.70
RB251-PN	10"	25	standard	phenolic based, non grooved		39	24	28.70
RB1251-P	10"	125	standard	phenolic based		52	24	28.70
-	20"		standard	cartridges		-	-	28.70