



Puretec Water Softening cartridges reduce hardness and scale deposits in water, leaving all the benefits of soft, gentle, clear water. Convenient, compact design means that softened water can be provided at point-of-use. SO cartridges available in 10, 20 heights and Standard, Maxi Plus diameters. Flow rates up to 70 litres per minute. Rechargeable resin media used.

Code	Size inches	Micron rating	Diameter	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
SO13	10"	5 post filter	standard, softening, taste, odour, reduction		15	30	61.12
SO201	10"	20 post filter	standard	<b>POPULAR</b>	15	12	43.82
SO202	20"	20 post filter	standard		30	8	67.02
SO20MP1	10"	20 post filter	maxi plus		35	8	67.53
SO20MP2	20"	20 post filter	maxi plus		70	4	134.87

See also SOL Series (page 29)



The Puretec SP cartridge series has special purposes in mind. They are selected by our technical team upon your individual requirement. Examples of SP cartridges are: Oil Absorbing for oil/water separation of run-off water, Tanin, Chloramine Removal, Neutralising and Radial Flow carbon cartridges for organic removal in liquids. Capacities, sizes and configurations depend on each application.

Code	Size inches	Diameter	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
SPCL1	10"	standard	chloramine removal cartridge		.7	12	95.27
SPCL2	20"	standard	chloramine removal cartridge		1.2	8	186.22
SPCLMP1	10"	maxi plus	chloramine removal cartridge		1.5	8	207.41
SPCLMP2	20"	maxi plus	chloramine removal cartridge		3	4	340.31
SPDA1	10"	standard	dealkalising cartridge	<b>NEW</b>	20	12	95.27
SPRF1	10"	standard	radial flow carbon cartridge		11	12	78.99
SPRF2	20"	standard	radial flow carbon cartridge		26	8	120.22
SPRFMP1	10"	maxi plus	radial flow carbon cartridge		38	8	121.79
SPRFMP2	20"	maxi plus	radial flow carbon cartridge		57	4	181.18
SPORMP2	20"	maxi plus	oil absorbing cartridge		40	4	247.24



The 10 inch Puretec Washable Screen cartridge is available in 60 and 250 micron ratings. It is ideal for the removal of high sediment and dirt, with flows up to 80 litres per minute. As it has a coarse filtration rating they are typically used for pump protection, aquaculture etc, and are not recommended as a final filter for drinking water.

Code	Size inches	Micron rating	Flow lpm	Box Qty	List (ea) Incl.GST	Purchase Qty (ea) as required	lpm	Qty	Incl.GST
WS6055	5"	250	standard	30	35				
WS2505	5"	250	standard				50	12	30.35
WS601	10"	60	standard			<b>POPULAR</b>	60	12	30.35
WS2501	10"	250	standard				80	12	30.35