



The Puretec HT100 is an alternative to the SS series. Capable of pressures up to 1380kpa at 93.3°C. Accepts flows up to 38 litres per minute and specific 10 inch cartridges depending upon application. HT100 with 3/4 inch connections offers excellent chemical

resistance through re-inforced nylon construction. Suitable for hot water, alcohol, inorganic chemicals, sea water, petroleum, oils and other liquids. Supplied with viton o-ring seal.

Code	Size inches	Connection	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
HT100	10"	3/4 inch	red bowl		38	8	275.67



Puretec SS Series housings are capable of temperatures up to 99°C at 2070kpa and a maximum flow of 45 litres per minute. SS housings are available in 10, 20 inch heights, 1/2, 3/4, 1 inch connections. They are suitable for the most demanding of applications

such as high pressure, temperature or corrosive, harsh conditions. The SS Series range comes complete with mounting bracket and spanner tool. Viton O-Ring for dependable seal is an option designed for extra chemical resistance.

It is important to note that each housing comes with drain plug for periodic draining and sprung knife edge seal for excellent filtration performance. Brass heads are standard, whilst stainless steel is an option.

Code	Size inches	Connection	Description	Purchase Qty (ea) as required	Flow lpm	Box Qty	List (ea) Incl.GST
SS115	10"	1/2 inch	brass head, <b>commercial box</b>		38	12	397.17
SS120	10"	3/4 inch	brass head, <b>commercial box</b> <b>POPULAR</b>		38	12	358.80
SS120-S	10"	3/4 inch	stainless steel head, <b>commercial box</b>		38	12	397.17
SS125	10"	1 inch	brass head, <b>commercial box</b>		38	12	397.17
SS220	20"	3/4 inch	brass head, <b>commercial box</b>		76	2	780.18
SS220-S	20"	3/4 inch	stainless steel head, <b>commercial box</b>		76	2	941.21
SS225	20"	1 inch	brass head, <b>commercial box</b>		90	2	972.88

Each Housing includes: spanner tool and mounting bracket kit, drain plug